#### Network Monitoring & Management Using Cacti

#### Network Startup Resource Center www.nsrc.org



These materials are licensed under the Creative Commons Attribution-NonCommercial 4.0 International license (http://creativecommons.org/licenses/by-nc/4.0/)



## Introduction

#### **Network Monitoring Tools**

Availability
 Reliability
 Performance

# *Cacti monitors the performance and usage of devices.*



## Introduction

- A tool to monitor, store and present network and system/server statistics
- Designed around RRDTool with a special emphasis on the graphical interface
- Almost all of Cacti's functionality can be configured via the Web.
- You can find Cacti here: <u>http://www.cacti.net/</u>





#### Introduction

**Cacti:** Uses RRDtool, PHP and stores data in MySQL. It supports the use of SNMP and graphics with RRDtool.



"Cacti is a complete frontend to RRDTool, it stores all of the necessary information to create graphs and populate them with data in a MySQL database. The frontend is completely PHP driven. Along with being able to maintain Graphs, Data Sources, and Round Robin Archives in a database, cacti handles the data gathering. There is also SNMP support for those used to creating traffic graphs with MRTG."



## Getting RRDtool

- Round Robin Database for time series data storage
- Command line based
- From the author of MRTG
- Made to be faster and more flexible
- Includes CGI and Graphing tools, plus APIs
- Solves the Historical Trends and Simple Interface problems as well as storage issues



?Dtool here: http://oss.oetiker.ch/rrdtool/



#### **RRDtool Database Format**



Medium length data averaged to one entry per half hour for the last 5 hours (6:10)



## **General Description**

- 1. Cacti is written as a group of PHP scripts.
- The key script is "poller.php", which runs every 5 minutes (by default). It resides in /usr/share/cacti/site.
- 3. To work poller.php needs to be in /etc/cron.d/cacti like this:

MAILTO=root

\*/5 \* \* \* \* www-data php /usr/share/cacti/site/poller.php >/dev/null 2>/var/log/cacti/poller-error.log

- 4. Cacti uses RRDtool to create graphs for each device and data that is collected about that device. You can adjust all of this from within the Cacti web interface.
- 5. The RRD files are located in /var/lib/cacti/rra when cacti is installed from packages.



#### Advantages

## You can measure Availability, Load, Errors and more all with history.

- Cacti can display your router and switch interfaces and their traffic, including all error traffic as well.
- Cacti can measure drive capacity, CPU load (network h/w and servers) and much more. It can react to conditions and send notifications based on specified ranges.

#### Graphics

- Allows you to use all the functionality of rrdgraph to define graphics and automate how they are displayed.
- Allows you to organize information in hierarchical tree structures.

#### **Data Sources**

 Permits you to utilize all the functions of rrdcreate and rrdupdate including defining several sources of information for each RRD file.



## Advantages (continued)

#### **Data Collection**

- Supports SNMP including the use of php-snmp or net-snmp
- Update data sources via SNMP or define scripts to capture required data
- *cactid* implements SNMP routines in C with multi-threading

#### Templates

- Create templates to reutilize graphics definitions, data and device sources

#### **Cacti Plugin Architecture**

 Extends Cacti functionality. Many, many plugins are available. Part of the default Cacti installation in Ubuntu version 12 and above.

#### **User Management**

- Manage users locally or via LDAP
- Assign granular levels of authorization by user or groups of users.



#### Disadvantages

- Configuring Interfaces via the web interface is tedious
- Use provided command-line scripts instead
- Upgrading versions difficult if installed from source.

#### Advice:

For continuous use or large installations it is likely that you will be using scripts and tools to automate the configuration of Cacti.



## Steps to Add and Monitor Devices

#### PART II

Before we install Cacti we demonstrate how to use the interface to add and monitor some devices...



## Adding a Device via the Web Interface

#### **Management -> Devices -> Add**

Specify device attributes

- We'll add an entry for our gateway router, gw.ws.nsrc.org\*

1		dian ti - Minaut	la filiatela (filial) (company) is a	0		
He Edit View H	igtory Bookmarks Jools Help					
* * - 2	💿 🚔 🔛 http://server/cacti/ho	st.php?host_status-	-16hest_template_id-86h	ast_rows-appletts im	Tel City coopie	🔍 🕰
WOLC: Gestión A	e 32 🧠 interest Sectory (i 32	int inside a set /	SE I W Linethal My SQL	issues all se must	×	Henry Marsh, Keyn 34
contain 1 ann						
proprie . p. Denines						Longound in our extension to the
	An and a second s					
New Graphs	Type: Local Linux Machine	0 Bhetsel Arty	© Berrs. 20 Rows	2 Beerstei	10	go slear
Graph Hartsgrowers	< C Providence		Bhowing Hows	THE T OF L [1]		Nest >>
Data Gaarras	Concernantian **	III Graphs Date	a Galantina - Martina - Marattala	and more dealers of	arrent (ma) Arrenge	(ma) Associately
Dervitante	Lastallaset.	1 4 5	up é	122.0.0.1 4	-01 - 1.01	100
College Gross Maddingsha	A STANDARD		Showing Rowe	1 to F to F iF i		NBNI 30-
Data Gaurian	Le.			Character and	aution Debrie	00
Graph Templates						
Hand, Terrapietate						
Dista Templates						
Antipatrick / English / E						
Done				* Apeche/2.2.0 1	192.169.0.2 🚥 🐙	- 1005 - OL M

\*Actual device name may be different.



### Add Devices (2)

Devices [edit: Gateway Router]		
General Host Options		
Description Give this host a meaningful description.	Gateway Router	
Hostname Fully qualified hostname or IP address for this device.	gw.ws.nsrc.org	
Host Template Choose what type of host, host template this is. The host template will gover what kinds of data should be gathered from this type of host.	m Cisco Router	
Disable Host Check this box to disable all checks for this host.	Disable Host	
Availability/Reachability Options		1921-01 1921 - 1921 - 1921 - 1921 - 1921 - 1921 - 1921 - 1921 - 1921 - 1921 - 1921 - 1921 - 1921 - 1921 - 1921
Downed Device Detection The method Cacti will use to determine if a host is available for polling. NOTE: It is recommended that, at a minimum, SNMP always be selected.	Ping and SNMP	Menu changes after you select SNMP
Ping Method The type of ping packet to sent. NOTE: ICMP on Linux/UNIX requires root privileges.	UDP Ping	version below:
Ping Port TCP or UDP port to attempt connection.	23	
Ping Timeout Value The timeout value to use for host ICMP and UDP pinging. This host SNMP timeout value applies for SNMP pings.	400	
Ping Retry Count After an initial failure, the number of ping retries Cacti will attempt before failing.	1	
SNMP Options		
SNMP Version Choose the SNMP version for this device.	Version 2	
SNMP Community SNMP read community for this device.	NetManage	
SNMP Port Enter the UDP port number to use for SNMP (default is 161).	161	
SNMP Timeout The maximum number of milliseconds Cacti will wait for an SNMP response (does not work with php-snmp support).	500	
Maximum OID's Per Get Request Specified the number of OID's that can be obtained in a single SNMP Get request.	10	
Additional Options		
Notes Enter notes to this host.		
		cancel create



## Add Devices (3)

- Host Template: *ucd/net SNMP Host* is recommended for servers to include disk definitions.
- Choose SNMP version 2 for this workshop.
- For "Downed Device Detection" we recommend either using *Ping and SNMP*, or just *Ping*.
- Use "NetManage" for the "SNMP Community" string.

SNMP access is a security issue:

- Version 2 is not encrypted
- Watch out for globally readable "public" communities
- Be careful about who can access r/w communities.
- Replace "xxxxxx" with your local public r/o string



## Add Devices (4)

For a router you may see *a lot* of potential network interfaces that are detected by SNMP.

Associated Data Queries				
Data Query Name	Debugging	Re-Index Method	Status	
1) Karlnet - Wireless Bridge Statistics	(Verbose Query)	Uptime Goes Backwards	Success [0 Items, 0 Rows]	o 🗙
2) SNMP - Interface Statistics	(Verbose Query)	Uptime Goes Backwards	Success [59 Items, 7 Rows]	) o <b>x</b>
Add Data Query: Netware - Get Available Volumes	\$	Re-Index Method: Uptime	Goes Backwards	add
				cancel save

# Your decision is to create graphs for all of these are not. Generally the answer is, "Yes" – Why?



## **Create Graphics**

- Chose the "Create graphs for this host"
- Under Graph Templates generally check the top box that chooses *all* the available graphs to be displayed.
- Press Create.
- You can change the default colors, but the predefined definitions generally work well.



## Create Graphics (2)

#### Save Successful.

#### Gateway Router (gw.ws.nsrc.org)

#### **SNMP Information**

System:Cisco IOS Software, 1841 Software (C1841-ADVIPSERVICESK9-M), Version
www.cisco.com/techsupport Copyright (c) 1986-2006 by Cisco Systems,
Inc. Compiled Tue 28-Feb-06 21:03 by alnguyen
Uptime: 24881862 (2 days, 21 hours, 6 minutes)
Hostname: sanog17-2.learn.ac.lk
Location:
Contact:



#### Ping Results

UDP Ping Success (1.19 ms)

Devices [edit: Gateway Router]	
General Host Options	
Description Give this host a meaningful description.	Gateway Router
Hostname Fully qualified hostname or IP address for this device.	gw.ws.nsrc.org
Host Template Choose what type of host, host template this is. The host template will govern what kinds of data should be gathered from this type of host.	Cisco Router



#### Create Graphics (3)

Gateway Router (gw.ws.nsrc.org) Cisco Router			
Host: Gateway Router (gw.ws.nsrc.org) 🗘 Graph Types: All	*Edit this Host *Create New Host		
Graph Templates			
Graph Template Name	☑		
Create: Cisco - CPU Usage	<b>I</b>		
Create: (Select a graph type to create)			

Data	Query	[SNMP - Interface	Statistics]						0
Index	Status	Description	Name (IF-MIB)	Allas (IF-MIB)	Туре	Speed	Hardware Address	IP Address	2
1	Up	FastEthernet0/0	Fa0/0		ethernetCsmacd(6)	100000000	00:24:97:5C:C0:D2	10.10.0.254	
2	Up	FastEthernet0/1	Fa0/1	connection to LEARN VPLS	ethernetCsmacd(6)	10000000	00:24:97:5C:C0:D3	192.248.5.1	
3	Up	NullO	Nu0		other(1)	4294967295			
4	Up	Tunnel0	Tu0		tunnel(131)	9000			
5	Up	Tunnel1	Tu1		tunnel(131)	9000			
6	Up	FastEthernet0/0.254	Fa0/0.254		l2vlan(135)	10000000	00:24:97:5C:C0:D2	10.10.254.254	
L,					Select a	graph type	In/Out Bits		ð
				Use 64-bit Counters fo	or Gigabit device	es	cano	el creat	e



### Create Graphics (4)

console gra	phs	
Console -> Create New	Graphs -> Create Graphs from Data Query	Logged in as admin (Logout)
Create	Create Graph from 'Linux - Memory Usage'	
New Graphs Hanagement	Create Graph from 'Unix - Load Average'	
Graph Management Graph Trees	Create Graph from 'Unix - Logged in Users'	
Data Sources	Graph Iteme [Template: Unix - Logged in Users]	
Devices Collection Methods	Legend Color The color to use for the legend.	4668E4   C
Data Queries Data Input Nethods	Create Graph from 'Unix - Processes'	
Templates Graph Templates	Graph Taxes (Template: Unix - Processes) Legend Color The sector for the legend	<b>F51D30</b>   ♀ ]
Host Templates	The color to use for the regena.	
Data Templates	Create 1 Graph from 'Unix - Get Mounted Partitions'	
Emport Templates		cancel create
Export Templates		
Configuration		
Utilities		
System Utilities		
User Nanagement		
Logout User		
Ŷ		

You'll see this screen later when you are creating graphics for hosts vs. routers



## View the Graphics

- Place the new device in its proper location in your tree hierarchy.
- Building your display hierarchy is your decision. Try drawing this out on paper first.
  - -Under Management I Graph Trees select the Default Tree hierarchy (or, create one of your own).



#### **Graphics Tree**

First, press "Add" if you want a new graphing tree:

Graph Trees	Add
Name	
Default Tree	×

Second, name your tree, choose the sorting order (the author likes Natural Sorting and press "create":

Graph Trees [new]	
Name A useful name for this graph tree.	NetManage Routers
Sorting Type Choose how items in this tree will be sorted.	Numeric Ordering
	cancel create



#### **Graphics Tree**

Third, add devices to your new tree:

Save Successful.		
Graph Trees [edit: NetManage Routers]		
Name A useful name for this graph tree.	NetManage Routers	
Sorting Type Choose how items in this tree will be sorted.	Natural Ordering	
Tree Items		Add
++		
Item No Graph Tree Items	Value	
	car	icel save

Once you click "Add" you can add "Headers" (separators), graphs or hosts. Now we'll add Hosts to our newly created graph tree:





## Graphics Tree with Two Devices

console graphs	settings 🕥 🚍 🟊
Graphs -> Tree Mode	Logged in as admin (Logout)
Default Tree <b>Host:</b> Localhost •••• NetManage Routers	Presets:       Last Day       From:       2011-01-12 08:40       To:       2011-01-13 08:40       To:       4 1 Day       To:       refresh       clear         Search:       Graphs per Page:       10       Thumbnails:       go       clear
Host: Gateway Router	Showing All Graphs
	Tree: NetManage Routers-> Host: Gateway Router
	Graph Template: Cisco - CPU Usage
	Gateway Router - CPU Usage

- Our graphics tree just after the first two devices were added.
- So far, graphics are empty the first data can take up to 5 minutes to display.
- Cacti graphs are stored on disk and updated using RRDTool via the poller.php script, which, by default, is run every five minutes using cron.



#### **Initial Graphs**





#### See Tendencies Over Time





## Next Steps

- There are a number of popular Cacti plugins, such as:
  - Settings
  - thold
  - PHP Weathermap
- A good place to start is http://cactiusers.net/ and Google.
- To send email to RT from Cacti via rt-mailgate you can use the Cacti "settings" plugin: http://docs.cacti.net/plugin:settings
- Automate device and graph creation using available command-line scripts in /usr/share/cacti/cli, such as:
  - add\_devices.php
  - add\_graphs.php
  - add\_tree.php



### Conclusions

- Cacti is very flexible due to its use of templates.
- Once you understand the concepts behind RRDTool, then how Cacti works should be (more or less) intuitive.
- The visualization hierarchy of devices helps to organize and locate new devices quickly.
- It is not easy to do a rediscover of devices.
- To add lots of devices requires automation. Software such as Netdot, Netdisco, IPPlan, TIPP can help – as well as local scripts that update the Cacti back-end MySQL database directly.



#### References

- Cacti Web Site: http://www.cacti.net/
- Plugin Documentation http://docs.cacti.net/plugins
- Cacti Discussion Group: http://forums.cacti.net/
- Cacti Users Plugin Architecture Home http://cactiusers.org/



#### **Cacti Installation and Configuration**

#### **Workshop Labs**



